

10+1

AVAILABLE IMMEDIATELY*

Megger®

TAKE ADVANTAGE OF OUR 10 + 1 DEALS.
BUY 10 UNITS OF A PRODUCT AND
GET ONE FOR FREE.

LASER DISTANCE METER

MLM50

**10+1
DEAL**



- 50 m Range
- Accuracy 1.5 mm (up to 10 m range)
- Single measurement mode
- Continuous measurement mode
- Automatic Max/Min
- Area Calculation
- Volume Calculation
- Meters, Feet & Inch Ranges
- 20 measurement memory
- Front or rear measurement reference
- Built-in spirit level
- IP54
- Supplied with protective belt pouch

2-POLE TESTER

TPT420

**10+1
DEAL**



- CAT IV / 1000 V
- IP64 Rated
- 12...1000 V AC
- 12...1500 V DC
- LED and LCD Display
- Continuity test function with visual and acoustic indication
- Voltage indication with no batteries
- Single pole voltage test
- Phase rotation indication
- Integrated torch light
- Supplied with protective carry pouch

DIGITAL MULTIMETER

AVO410

**10+1
DEAL**



- 6000 count backlit digital display
- True RMS reading on AC mode
- 1000 V DC / 750 V AC ranges
- 10 A AC / DC ranges
- Resistance, frequency and capacitance ranges
- CAT IV 600 V

* while stocks last / end of promotion: 30.04.22

5+1 AVAILABLE IMMEDIATELY*

TAKE ADVANTAGE OF OUR 5 + 1 DEALS.
BUY 10 UNITS OF A PRODUCT AND
GET ONE FOR FREE.

THERMAL CAMERA FOR FAST
LOCALIZATION OF HOTSPOTS

TC3231



5+1
DEAL

- Full thermal image for IR temperature measurement
- Measurement range -20 ° to 300 °C
- Adjustable emissivity
- Micro SD memory for storing up to 6000 images
- Max/Min Measurements on screen
- Hot & Cold Spot tracking on screen
- Full image blending and selectable measurement distance of 0,5 m, 1 m, 2 m or 3m for greater accuracy

POWER CLAMP
WITH MEGGER LINK APP

DPM1000



5+1
DEAL

- AC/DC Voltage to 1000 V
- AC/DC Current to 1000 A
- True RMS
- Resistance 100 kΩ
- LCD Display
- Phase rotation indication
- Auto backlight display
- Frequency measurement
- Capacitance measurement
- Power Factor Measurement
- Watt measurement to 1MW
- Harmonic measurement
- Harmonic distortion
- Diode test
- Non-contact volt alert
- Continuity Beeper
- Data Hold/Min-Max/Peak Hold
- Bright LED torch
- Temperature to 1000° C
- Hard carry case
- CAT IV 600V Rating
- Supplied with carry case

DIGITAL / ANALOGUE INSULATION
AND CONTINUITY TESTERS

MIT230



5+1
DEAL

- Insulation testing to 1000 MΩ
- Continuity testing at 200 mA down to 0.01 Ω
- Live circuit warning (voltage display) and test inhibit
- Digital/analogue display
- Alkaline or rechargeable batteries
- -10 °C to +55 °C operating temperature
- CAT III 600 V
- Conforms to EN 61557

* while stocks last /
end of promotion: 30.04.22

AC NON-CONTACT
VOLTAGE DETECTOR

VF6 EX & VF5

- Hazardous area rated (only VF6 EX)
- AC non-contact voltage detector
- 12 V – 1000 V voltage range
- Screw-on battery cover
- Built-in bright-white LED torch

2x12s PACK 10% Extra

- Visual, audible and vibration warning of low and medium voltages
- CAT IV 1000 V
- IP67